

Perovskite Cell Glass Cleaning Equipment

SC-SA LAR

# 特点描述

- 带式毛刷代替传统交替排布毛刷;
- 下料段EUV或大气AP进行TCO玻璃表面改性;
- 干段磁力轮传动,湿段滴水润滑+PE斜齿轮传动;
- UPE防静电材质,高精密AK风刀切水干燥。

#### Features

- Belt brush replaces the traditional alternating brush;
- EUV or AP for TCO glass surface modification;
- Dry section driven by magnet coupling gear, wet section lubricated with drip water + PE helical gear transmission;
- UPE anti-static material, High-precision air knife used to block water.

# 技术性能

Uptime≥98%; 洗净率≥98%; (小微粒去除率>98%,中颗微粒: 0ea,大颗微粒: 0ea); 接触角<15度(初始条件: 接触角<60度); 玻璃基板尺寸: 2000mm(L)x1000mm(W)(短边进), 厚度2mm~5mm; 每小时65片(55秒/片),玻璃间距500mm,传送速度最大4m/min。

### 技术参数 Parameter

项目 Item	数值 Valu
设备尺寸 Layout dimension	10410mn



#### Performance

Uptime ≥98%; Purification rate ≥98%(Small particulate > 98%, Medium particulate: 0 EA, Large particulate: 0 EA); Contact angle< 15 °(Initial: contact angle < 60°); Glass substrate size: 2000mm(L)x1000mm(W) (Short side in), Thickness 2mm~5mm; 65 pcs/hour (55 s/pc), Glass pitch 500mm, maximum transmission speed 4m/min。

#### alue

nm\*3100mm\*2200mm (含自动化 Automation included)